



PT-PSE106SAR48-24

Isolated Ground 24V PoE Injector

Product Overview

PT-PSE106SAR48-24 is a single port PoE Injector. It provides 24Vdc, 1.25A power for remote PDs over 2-pairs output with 6KV (10/700us) surge protection. It supports both 10/100Base-T and Gigabit device. It works for 30W PoE PDs, such as wireless APs, ONU IP phone and other power Ethernet terminals.

PT-PSE106SAR48-24 is designed for indoor use. It works with input voltage of 44-72Vdc. It will directly power PDs without detection. The effective distance is 100 meters over Cat5e/Cat6 cables.

Product Profile



1.LAN: Data Input Port 2.PoE: Data & Power Output Port

3. Power Indicator



4. PoE Load Indicator

6. DC Input Negative Pole


7. DC Input Positive Pole

without detection. The effective distance is 100 meters over Cat5e/Cat6 cables.



5,8. Mounting Hole

Product Working Diagram



Specification

Standard

- IEEE802.3 10Base-T Ethernet
- IEEE802.3u 100Base-Tx Fast Ethernet
- IEEE802.3ab 1000Base-T Gigabit Ethernet
- RoHS Compliance
- WEEE Compliance

Input & Output

Input: 44-72Vdc 2.5A
Output: 24Vdc 1250mA
Power Pins: 4/5(+), 7/8(-)
Data Speed: 10/100/1000Mbps

Working Environment

- Operating Temperature: 0 ℃ to 40 ℃

- Operating Humidity: 20% to 80%, non-condensation

- Storage Temperature: -20 ℃ to 70 ℃

- Storage Humidity: 10% to 90%, non-condensation

- Operating Altitude: up to 2000meters

PoE Surge Protection

- Protected line: 1,2,3,4,5,6,7,8

- Common mode surge protection(10/700us): 6KV

- Differential mode surge protection (10/700us): 1.5KV

Mechanical Characteristics

- Case: Plastic - Color: Black

- Mounting: Wall-mounted

- IP Rated: IP40

- Size: 120mm X 125mm X 44mm

- Weight: 350g

EMI

- FCC CFR47 Part 15, EN55024, EN55032

EMS


- IEC61000-4-2(ESD) ± 6kV(contact), ±8kV(air)
- IEC61000-4-3(RS) 10V/m(80MHz~2GHz)
- IEC61000-4-4(EFT) Power Port: ±2kV; Data Port:±1kV
- IEC61000-4-5(Surge) Power Port:±1kV/DM, ±2kV/CM
- IEC61000-4-6(CS) 10V(150kHz~80MHz)

Immunity

- IEC60068-2-6(Vibration)
- IEC60068-2-27(Impact)
- IEC60068-2-32(Free Fall)

LED Indicator

Power Indicator : GreenPoE Load Indicator : Green



Order Info. PT-PSE106SAR48-24 24Vdc/1.25A/1000M/(4,5+,7,8-) /Surge Protection/Passive

Packing

PT-PSE106SAR48-24 Power Cord x 1 (Optional) Manual x 1



This document belongs to PROCET company. It is not allowed to reproduce and modify without the original author's permission. It is PROCET's policy to improve its products as new technology, components, software, and firmware at any time. PROCET, therefore, reserves the right to change specifications without prior notice. (2018.05)