


## PoE to Apple Lightning Adapter

### Product Overview

PTAP-AF is an indoor rated PoE to Apple lightning adapter specially designed for complex backhaul and networking application. Enclosed in an IP40 fire retardant plastic case with compact design.

It works as a converter to get power and data from PoE injector or PoE Switch of 802.3af/at over RJ45 connector then deliver power and data all-in-one to PDs via lightning connector cable.




**PTAP-AF**

Specially designed for iPad, iPhone with the lightning connector.

The Lightning Male connector not only deliver power at 5Vdc, 2.0A, but also provide Ethernet data signal at 10/100Mbps. For planning purposes, the effective distance is 100 meters via Cat5e/Cat6 cables from Ethernet data source to the Apple lightning Adapter.


### Product Profile



1. PoE: Data&Power input port  
2. 4. Mounting holes

3. Power output indicator  
5. Apple Lightning Male port

### Product Working Diagram



## Specification

### Standard

- IEEE802.3 10Base-T Ethernet
- IEEE802.3u 100Base-Tx Fast Ethernet
- Support PoE injector with IEEE802.3af/at
- RoHS Compliance
- WEEE Compliance

### Input & Output

- Input :40-57Vdc PoE injector/PoE Switch 802.3af/at
- Input Power Pins: 4/5(+), 7/8(-) or 3/6(+),1/2(-)
- Output: 5Vdc 2.0A
- Data Speed: 10/100Mbps

### Working Environment

- Operating Temperature: 0℃ to 55℃
- Operating Humidity: 20% to 80%, non-condensation
- Storage Temperature: -20℃ to 70℃
- Storage Humidity: 10% to 90%, non-condensation
- Operating Altitude: up to 2000meters

### Mechanical Characteristics

- Case: Plastic
- Color: white
- Mounting: Wall-mounted
- IP Rated: IP40
- Size: (81.3+125.09)mm X 34.7mm X 19mm
- Weight: 200g
- Connectors: RJ45 Female\*1,  
Apple Lightning Male\*1

### EMI

- FCC CFR47 Part 15, EN55032, EN55035

### EMS


- IEC61000-4-2(ESD) Air discharge: 8kV,  
Contact discharge: 4kV, Performance B
- IEC61000-4-3(RS) 80~1000MHz,3V/m,80%AM(1kHz),  
Performance A
- IEC61000-4-4(EFT) AC Power line: 1kV, Performance B  
DC Power line:0.5kV,Performance B  
Signal line:0.5kV, Performance B

### Immunity

- IEC60068-2-6(Vibration)
- IEC60068-2-27(Impact)
- IEC60068-2-32(Free Fall)

### LED Indicator

- Power output Indicator : Green



**Order Info.** PTAF-AF

5Vdc/2.0A/10/100Mbps/4,5(+),7,8(-) or 3,6(+),1,2(-)/PoE to Apple Lightning

**Packing.** PTAF-5V  
Manual x 1

This document belongs to PROCET company. It is not allowed to reproduce and modify without the original author's permission. It is PROCET's policy to improve its products as new technology, components, software, and firmware at any time. PROCET, therefore, reserves the right to change specifications without prior notice. (2021.11)