



## PT-PR02G

### Dual-Port PoE Surge Protector

#### Product Overview

PT-PR02G is Dual-port PoE surge protector, which has 4 pairs RJ45 ports can protect up to four separate Network cables. Each pair port can be PoE in or PoE out and supports 8 lines network signals and provides surge protection for PoE wires.


The maximum common mode surge voltage is 20KV(10/700us) and differential mode surge voltage is 1.5KV(10/700us). It supports 10/100/1000Mbps of data speed. It also supports PoE wires with IEEE802.3af/at/bt or PoE++ standard and protects your device against surge damage.

PT-PR02G is designed for indoor use with Zinc alloy shell, which works with 60Vdc Max voltage and operates under -40 °C to 85 °C. It is connected to network over Cat5e/Cat6 cables with RJ45 connector conveniently and tightly.

This model can be placed on desk or equip standard DIN rail mounting bracket which can easily jam into the guide rail. The bracket is very flexible which can be fixed on back or side. There are also wall mounting tabs on either side if you do not like it to be rail-mounted.




#### Product Profile



1. Earth  
2.3.4.5. Surge Protector Input Or Output Port

6.DIN Rail Mounting Bracket(Can be removed)  
7.8.Mounting tabs

#### Product Working Diagram



This document belongs to PROCET company. It is not allowed to reproduce and modify without the original author's permission. It is PROCET's policy to improve its products as new technology, components, software, and firmware at any time. PROCET, therefore, reserves the right to change specifications without prior notice. (2025.05)