

# PT-PSE109GBROA-VI PoE Injector


#### **Product Introduction**

The PT-PSE109GBROA-VI is a compact, single-port high power PoE injector delivering up to 95W to IEEE 802.3bt-compliant Powered Devices such as IP cameras, wireless APs, IoT devices, POS terminals, and digital displays. It is ERP Energy Efficiency Class VI compliant for reduced power consumption and greater efficiency.

With an intelligent detection chip, it identifies and classifies devices before powering, protecting non-PoE equipment. It supports 10/100/1000Mbps data rates and transmits up to 100m over Cat5e/Cat6 cables.

Featuring a 90-264VAC input range, 6kV surge protection, and a flame-retardant IP20 enclosure, it is designed for indoor wall-mount installation and operates in temperatures from  $-40^{\circ}$ C to  $+65^{\circ}$ C.

#### **Product Connection Diagram**



### **Product Specification**

| ltem                | PT-PSE109GBROA-VI   |  |
|---------------------|---|--|
| Ports               | AC Input*1 PoE*1 LAN*1  |  |
| PoE Standard        | IEEE802.3af/at/bt Power over Ethernet   |  |
| Input               | 90-264Vac   |  |
| PoE Output          | 55Vdc 1.72A 95W Max   |  |
| Power Pins          | 4/5(+),7/8(-) and 3/6(+),1/2(-)   |  |
| Energy Effiency     | ⇒88%  |  |
| NLPC                |   |  |
| NLPC                | ≤0.21W  |  |
| Surge Protection    | AC Port Common Mode: 6KV Differential Mode: 4KV PoE Port Common Mode: 6KV Differential Mode: 1.5KV            |  |
| EER                 | ERP Level VI  |  |
| Network Protocol    | IEEE802.3 10Base-T Ethernet<br>IEEE802.3u 100Base-Tx Fast Ethernet<br>IEEE802.3ab 1000Base-T Gigabit Ethernet |  |
| Data Rate           | 100/1000Mbps  |  |
| Operate Temperature | -40°C — 65°C  |  |
| Operate Humidity    | 20%-80%, non-condensing   |  |
| Operate Altitude    | Below 5000 meters   |  |
| Storage Temperature | -40°C — 85°C  |  |
| Storage Himidity    | 10%-90%, non-condensing   |  |
| Enclosure           | Black Metal Case  |  |
| Installation        | Wall-Mounted Installation   |  |
| IP Rate             | IP20  |  |
| Size & Weight       | 213.9mm X 134mm X 41mm(1120g)   |  |
| Certification       | CE/FCC/ERP Level VI   |  |

## **Model Comparison Chart**

| ltem          | PT-PSE109GBROA-VI                     | PT-PSE109GBROA-10-VI        |  |
|---------------|---------------------------------------|-----------------------------|--|
| Ports         | AC Input*1 PoE*1 LAN*1                |                             |  |
| PoE Standard  | IEEE802.3af/at/bt Power over Ethernet |                             |  |
| Data Rate     | 100/1000Mbps                          | 100/1000Mbps 2.5G/5G/10Gbps |  |
| Input         | 90~264Vac                             |                             |  |
| IP Rates      | IP20                                  |                             |  |
| Size & Weight | 213.9mm X 134mm X 41mm(1120g)         |                             |  |